

## Jobigo 38610TPGMU

Safety boot for winter use. Adjustable Velcro fastening. Drawstring at the top of the boot leg.

**Toe cap:** aluminium (200J/15kN)  
**Nail protection:** composite textile midsole (1100N)  
**Upper:** black PU-coated leather / textile  
**Lining:** textile  
**Sole:** polyurethane, tread of heat-resistant nitrile rubber (HRO)  
**Protection level:** EN ISO 20345 S3+HRO+SRC  
**Sizes:** 35 – 48



## Jobigo 38620

Safety boot for indoor and outdoor use. Easy to put on and clean. Fulfills the hygiene requirements of food industry. Seams open downwards.

**Toe cap:** aluminium (200J/15kN)  
**Upper:** black PU-coated leather  
**Lining:** textile  
**Sole:** polyurethane  
**Colours:** black (MU), white (VA)  
**Protection level:** EN ISO 20345 S2+SRC  
**Sizes:** 35 – 48



## Jobigo 38640FPGMU

Water-resistant safety boot in accordance with the requirements of the Finnish Army. LajaTex membrane lining with a water-resistant taped seam structure.

**Toe cap:** aluminium (200J/15kN)  
**Nail protection:** steel midsole (1100N)  
**Upper:** water-resistant black leather  
**Lining:** sock structure, membrane lining with water-resistant taping  
**Sole:** polyurethane, tread of heat-resistant nitrile rubber (HRO)  
**Protection level:** EN ISO 20345 SB+E+P+WR+HRO+SRC  
**Sizes:** 35 – 48



## Jobigo 38650TPGMU

Safety boot for outdoor use. With laces and zipper. Warm membrane lining.

**Toe cap:** aluminium (200J/15kN)  
**Nail protection:** composite textile midsole (1100N)  
**Upper:** black PU-coated leather  
**Lining:** membrane lining, without water-resistant taped seams  
**Sole:** polyurethane, tread of heat-resistant nitrile rubber (HRO)  
**Protection level:** EN ISO 20345 S3+HRO+SRC  
**Sizes:** 35 – 48



## Jobigo 38660PGMU

Safety boot for indoor and outdoor use. Suitable for welders.

**Toe cap:** aluminium (200J/15kN)  
**Upper:** black full-grain leather, heat-resistant properties. Heat-resistant threads and metal reinforcements in the seams.  
**Lining:** textile  
**Sole:** polyurethane, tread of heat-resistant nitrile rubber (HRO)  
**Protection level:** EN ISO 20345 S2+HRO+SRC  
**Sizes:** 39 – 48



## Jobigo 38670TPGMU

Safety ankle boot for indoor and outdoor use. With laces and zipper.

**Toe cap:** aluminium (200J/15kN)  
**Nail protection:** composite textile midsole (1100N)  
**Upper:** black PU-coated leather  
**Lining:** mesh textile  
**Sole:** polyurethane, tread of heat-resistant nitrile rubber (HRO)  
**Protection level:** EN ISO 20345 S3+HRO+SRC  
**Sizes:** 35 – 48



## Jobigo 38680TPGMU

Safety ankle boot for indoor and outdoor use. With zipper.

**Toe cap:** aluminium (200J/15kN)  
**Nail protection:** composite textile midsole (1100N)  
**Upper:** black PU-coated leather, heat-resistant threads  
**Lining:** textile  
**Sole:** polyurethane, tread of heat-resistant nitrile rubber (HRO)  
**Protection level:** EN ISO 20345 S3+HRO+SRC  
**Sizes:** 35 – 48



## Jobigo 38660FPGMU

Safety boot for indoor and outdoor use. Suitable for welders.

**Toe cap:** aluminium (200J/15kN)  
**Nail protection:** steel midsole (1100N)  
**Upper:** black full-grain leather, heat-resistant properties. Heat-resistant threads and metal reinforcements in the seams.  
**Lining:** textile  
**Sole:** polyurethane, tread of heat-resistant nitrile rubber (HRO)  
**Protection level:** EN ISO 20345 S3+HRO+SRC  
**Sizes:** 39 – 48

**Insole:** 126008 Safety soft



**Sole:** Jobigo, black

